GEORGIA INSTITUTE OF TECHNOLOGY OFFICE OF CONTRACT ADMINISTRATION SPONSORED PROJECT INITIATION

ac	1
agr	170cc 1
1976	- att

h.

Date: June 29,

Project Title:

Testing Various Blends of Pyrolytic Oil Residuals as Asphalt

Extenders

Project No:

A-232-786

Project Director: Dr. J. A. Knight

Sponsor: American Can Company; Princeton, New Jersey

Agreement Period:

June 10, 1976 From

Until

Open

Type Agreement: Letter dated; 6/10/76

Amount:

\$350.00

Reports Required: as requested

Sponsor Contact Person (s):

Technical Matters

Contractual Matters (thru OCA)

Dr. D. H. Johns Research & Development Princeton Laboratory American Can Company P.O. Box 50 Princeton, New Jersey 609-921-2510

Defense Priority Rating: None

Assigned to: Productivity/Technology Applications (School/Laboratory)

COPIES TO:

Project Director Division Chief (EES) School/Laboratory Director Dean/Director-EES **Accounting Office Procurement Office** Security Coordinator (OCA)

Library, Technical Reports Section Office of Computing Services Director, Physical Plant **EES Information Office** Project File (OCA) Project Code (GTRI)

Other

Reports Coordinator (OCA)

GEORGIA INSTITUTE OF TECHNOLOGY OFFICE OF CONTRACT ADMINISTRATION

SPONSORED PROJECT TERMINATION

3 (19)		Date: 1/2	5/77
	roject Title: Testing Various Blends	of Prolytic Oil Posiduos as	Acabalt Extandars
5 1 1	reject the lesting various brends	of Fyrotytic off Residues as I	sphart Extenders.
	oject No: A-232-786	•	•
) (27)	ject Director: Dr. J. A. Knight		
458	onsor: American Can Company; Pri	nceton, N.J. 08540	
e.B	ective Termination Date: Open		
Thanks.B	arance of Accounting Charges:		
binding.	ant/Contract Closeout Actions Remaining: P	roject has been completed.	
Imperfect volumes delay return of LIBRARY BINDERY CO. OF GA.	Final Invoice and Closing Doc	uments	
dela)	Final Fiscal Report	· 1	
les ER	Final Report of Inventions	t	
volumes BINDERY	Govt. Property Inventory & R	elated Certificate	
, Y E	Classified Material Certificate	·	
Imperfect		1, 1	
per KA	_ Other		
_E _E			
page?			5
itle page? ATIONAL			
itle ATIC		•	
+ +	L. Company		
and THE h			
ΒY	7. 1	-1 A - 11 - A	
9	signed to: Productivity and Techno	ology Applications (School/Labora	tory)
BOUND	PIES TO:		
ă	Project Director	Library, Tachnical Reports Section	
	Division Chief (EES)	Office of Computing Services	
	School/Laboratory Director	Director, Physical Plant	*
	Dean/Director—EES	EES Information Office	•
	Accounting Office Procurement Office	Project File (OCA) Project Code (GTRI)	
J.	Security Coordinator (OCA)	Other	
	Reports Coordinator (OCA)		· ·



ENGINEERING EXPERIMENT STATION GEORGIA INSTITUTE OF TECHNOLOGY • ATLANTA, GEORGIA 30332

September 20, 1976

Dr. D. H. Johns
Research & Development
Princeton Laboratory
American Can Company
P.O. Box 50
Princeton, New Jersey 08540

Dear Dr. Johns:

A report on the preparation of the blends of pyrolytic oil residues and asphalt AC-10 is enclosed. These blends were supplied to Dr. James Lai of the School of Civil Engineering for his testing program, which is not a part of this project, A-232-786. Dr. Lai will report on his work separately.

If you have any questions about the work, please let me know.

Sincerely,

James A. Knight, HEAD
WASTE UTILIZATION LABORATORY

JAK:bc

Enclosure



ENGINEERING EXPERIMENT STATION

September 8, 1976

PROJECT A-232-786

PREPARATION OF BLENDS OF ASPHALT AC-10 AND PYROLYTIC OIL RESIDUES

Dr. James A. Knight

Blends of two pyrolytic oil residues and asphalt AC-10 were prepared for consistency and durability tests. One pyrolytic oil residue, supplied by Mr. Del Lohuis, Tech-Air Corporation, was obtained by atmospheric distillation and identified as Sample 1715. The other sample, supplied by the Princeton Laboratory, American Can Company, was vacuum distilled and identified as M-33-70Z. Blends of each residue were prepared containing 15%, 30% and 55% by weight of the residue with asphalt AC-10. Asphalt AC-10 was obtained from the Georgia Highway Materials testing Laboratory and Koppers Asphalt Company of Conley, Georgia. Approximately 2600 g. of each blend was prepared by heating with stirring the appropriate quantity of residue and asphalt AC-10 to approximately 300°F. The mixtures were heated and stirred for approximately 20 minutes. The six blends along with an original sample of asphalt AC-10 were supplied on June 22nd to Dr. James Lai of the School of Civil Engineering, Georgia Tech, for testing.